

### Technical Specifications for Electric Driven Scissor Lift – Sky Jack 3226

Work Height	9.92 m
Raised Platform Height	7.92 m
Lowered Platform Height	1.14 m
Overall Width / Length	0.84 m x 2.32 m
Stowed Height (Rails Up / Down)	2.15 m x 1.91 m
Platform W/ L (Inside)	0.71 m x 2.13 m
Extension Deck (Roll Out)	0.91 m
Ground Clearance (Stowed / raised)	8.89 cm x 1.90 cm
Wheelbase	1.75 m
Weight	1,890 kg
Gradeability	30%
Turning Radius (Inside)	1.27 m
Turning Radius (Outside)	2.74 m
Lift Time (With Rated Load)	56 sec
Lower Time (With Rated Load)	42 sec
Drive Speed (Stowed) / (Raised)	3.2 km/h / 1.1 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	227 kg
Distributed Capacity	114 kg
Distributed Capacity (Ext Deck)	113 kg
Maximum # of Persons	2/0



### Technical Specifications for Electric Driven Scissor Lift – Sky Jack 4632

Work Height	11.75 m
Raised Platform Height	9.75 m
Lowered Platform Height	1.23 m
Overall Width	1.17 m
Overall Length	2.31 m
Stowed Height (Rails Up)	2.24 m
Stowed Height (Rails Down)	1.88 m
Platform Width (Inside Dimension)	1.07 m
Platform Length (Inside Dimension)	2.13 m
Extension Deck (Roll Out)	1.22 m
Ground Clearance (Stowed / Raised)	8.89 cm / 1.91 m
Wheelbase	1.75 m
Weight	2,302 kg
Gradeability	25%
Turning Radius (Inside) / (Outside)	1.21 m / 2.37 m
Lift / Lower Time	59 sec / 49 sec
Drive Speed (Stowed / Raised)	3.2 km/h / 1.1 km/h
Maximum Drive Height	Full Height
Distributed Capacity (Main)	204 kg
Distributed Capacity (Deck)	113 kg
Maximum # of Persons	2/1



### Technical Specifications for Electric Driven Scissor Lift – NetLift SEL X 8 DC

Work Height	9.9 MTR
Raised Platform Height	7.9 MTR
Lowered Platform Height	
Overall Width	0.76 MTR
Overall Length	2.07 MTR
Stowed Height (Rails Up)	2.08 MTR
Platform Width (Inside Dimension)	0.76 MTR
Platform Length (Inside Dimension)	1.88 MTR
Extension Deck (Roll Out)	0.9 MTR
Ground Clearance (Stowed / Raised)	01 MTR x 0.19 MTR
Wheelbase	1.58 MTR
Weight	1390 KG
Gradeability	25%
Turning Radius (Inside) / (Outside)	0.7 MTR x 2.5 MTR
Lift / Lower Time	28 / 30 sec
Drive Speed (Stowed / Raised)	4 km/h x 0.8 km/h
Capacity (Main)	230
Capacity (Deck)	113
Maximum # of Persons	2/1



### Technical Specifications for Electric Driven Scissor Lift – NetLift SEL 10 HD

Work Height	11.6 MTR
Raised Platform Height	9.6 MTR
Lowered Platform Height	2 MTR
Overall Width	1.15 MTR
Overall Length	2.72 MTR
Stowed Height (Rails Up)	2.4 MTR
Platform Width (Inside Dimension)	1.12 MTR
Platform Length (Inside Dimension)	2.5 MTR
Extension Deck (Roll Out)	0.9 MTR
Ground Clearance (Stowed / Raised)	0.11 x 0.019 MTR
Wheelbase	2.09 MTR
Weight	2670 kg
Gradeability	25 %
Turning Radius (Inside) / (Outside)	0.5 / 3 MTR
Lift / Lower Time	50 / 44 sec
Drive Speed (Stowed / Raised)	3.5 / 0.8 km/h
Capacity (Main)	460 KG
Capacity (Deck)	113 KG
Maximum # of Persons	2 / 1 (ins / out)

